Accessory Fitting Instructions

Thank you for choosing this Triumph genuine accessory kit. This accessory kit is the product of Triumph's use of proven engineering, exhaustive testing, and continuous striving for superior reliability, safety and performance.

Completely read all of these instructions before commencing the installation of the accessory kit in order to become thoroughly familiar with the kit's features and the installation process.


These instructions should be considered a permanent part of your accessory kit, and should remain with it even if your accessory equipped motorcycle is subsequently sold.

Headlight Bezel and Grille	
Kit Number	**Models**
36TA0046	Speed 400

Publication part number 9901220 Issue 1
© Triumph Designs Ltd. 2023

Parts supplied

36TA0046



1. Headlight grille and bezel	1 off	2. Headlight bowl fixings	2 off

⚠ WARNING

Fit only genuine Triumph accessories to those models approved by Triumph as listed in the associated Triumph fitting instructions.

The accessory kits covered in this instruction are designed for use on specific models of Triumph motorcycle. The accessory kits and the models applicable are listed at the start of the instruction. They should never be fitted to any other Triumph model or to any other manufacturer's motorcycle.

Fitting an accessory kit to a Triumph model not listed, or to any other manufacturer's motorcycle, will affect the performance, stability and handling of the motorcycle.

Failure to follow the advice above may lead to loss of motorcycle control which could result in serious injury or death.

⚠ WARNING

Always have Triumph approved parts, accessories and conversions fitted by a competent person with the specialist knowledge and technical understanding of motorcycles, such as an authorised Triumph dealer.

The fitment of parts, accessories and conversions by a person without the specialist knowledge and technical understanding of motorcycles may affect the handling, stability or other aspects of the motorcycle's operation.

Failure to follow the advice above may lead to loss of motorcycle control which could result in serious injury or death.

⚠ WARNING

A torque wrench of known accurate calibration must be used when fitting this accessory kit.

Failure to tighten any of the fasteners to the correct torque specification may affect motorcycle performance, handling and stability.

Failure to follow the advice above may lead to loss of motorcycle control which could result in serious injury or death.

⚠ WARNING

Make sure the motorcycle is stabilised and adequately supported.

Do not support the motorcycle on any ancillary component, the exhaust system or any other non structural parts of the motorcycle frame.

A correctly supported motorcycle will help prevent it from falling.

An unstable motorcycle may fall resulting in motorcycle damage, serious injury or death.

NOTICE

Triumph offers a broad range of approved genuine accessories for your motorcycle.

We cannot therefore cover all possible equipment variations in these instructions. For removal and installation of Triumph Genuine Accessories, always refer to the instructions supplied with the respective accessory kit.

To obtain additional copies of any Triumph accessory instructions, visit www.triumphinstructions.com or contact your authorised Triumph dealer.

Speed 400

1. Remove the seat as described in the Owner's Handbook.
2. Disconnect the battery as described in the Owner's Handbook.
3. Remove the headlight as described in the Service Manual.


NOTICE

With the headlight removed from the motorcycle, care should be taken to avoid damage to the lens.

Keep the lens clean and free from debris.

Cover the lens with a heavy cloth to avoid damage or scratches.


4. Remove and discard the headlight bezel fixings



IASM_00587

1. **Headlight bowl**
2. **Headlight bowl fixings**
3. **Headlight bezel**
4. **Bezel alignment feature**

5. Remove the headlight bowl from the headlight and bezel assembly (right hand side shown).



IASM_00588_1

1. **Headlight bezel**
2. **Headlight bowl**
3. **Headlight electrical harness**


⚠ CAUTION

Retaining clips are under tension and can cause injury if released suddenly.

Always wear suitable protective eye wear and release the retaining clips slowly.

Failure to follow the advice above could result in minor to moderate injury.


6. Release the retaining clips and remove the headlight from the headlight bezel. Retain the headlight bezel for reuse if the motorcycle is to be returned to its original condition.



IASM_00589

1. **Headlight**
2. **Headlight bezel**
3. **Alignment feature**
4. **Retaining clips**
5. **Clip locating points**


7. Collect the headlight grille and bezel assembly from the accessories kit.
8. Position the headlight into the headlight bezel, lining up the locating feature.
9. Make sure the retaining clips are positioned to the locating points and install the retaining clips.



IASM_00589_1

1. **Headlight**
2. **Headlight bezel**
3. **Alignment feature**
4. **Retaining clips**
5. **Clip locating points**


10. Fit the headlight bowl to the headlight and bezel assembly (right hand side shown).



IASM_00734

1. **Headlight bezel**
2. **Headlight bowl**

11. Collect and fit the headlight bowl fixings from the accessory kit and tighten to 0.7 Nm.



IASM_00735

1. **Headlight bowl**
2. **Headlight bowl fixings**
3. **Headlight bezel**
4. **Bezel alignment feature**

12. Fit the headlight as described in the Service Manual.
13. Reconnect the battery as described in the Owner's Handbook.
14. Check the operation of the headlight. Rectify if necessary.
15. Refit the seat as described in the Owner's Handbook.

⚠ WARNING

After fitting the accessory kit the motorcycle will exhibit new handling characteristics.

Operate the motorcycle in a safe area free from traffic to gain familiarity with any new characteristics.

Operation of the motorcycle when not familiar with any new handling characteristics may lead to loss of motorcycle control which could result in serious injury or death.

⚠ WARNING

If, after fitting this accessory kit, you have any doubt about the performance of any aspect of the motorcycle, contact a competent person with the specialist knowledge and technical understanding of motorcycles, such as an authorised Triumph dealer.

Riding a motorcycle when there is any doubt as to any aspect of the performance of the motorcycle may lead to loss of motorcycle control which could result in serious injury or death.

⚠ WARNING

Never ride an accessory-equipped motorcycle at speeds above 80 mph (130 km/h).

Remember that the 80 mph (130 km/h) limit will be reduced by the fitting of non-approved accessories, incorrect loading, worn tyres, overall motorcycle condition and poor road or weather conditions.

The presence of accessories will cause changes in the stability and handling of the motorcycle. Failure to allow for changes in motorcycle stability may lead to loss of motorcycle control which could result in serious injury or death.

⚠ WARNING

High-speed operation should only be attempted by riders who have been instructed in the techniques necessary for high-speed riding and are familiar with the motorcycle's characteristics in all conditions.

Only operate this Triumph motorcycle at high speed in closed-course, on-road competition or on closed-course racetracks.

High-speed operation in any other circumstances is dangerous and may lead to loss of motorcycle control which could result in serious injury or death.

NOTICE

The motorcycle must not be operated above the legal road speed limit except in closed-course conditions.